

Product Information Sheet

Name: Drain Dry (Dryfast) Foam

Description:

- Porous, open cell, reticulated polyurethane foam engineered for quick water drainage and airflow
- Recommended for outdoor cushions, boat seating, and marine applications
- Unique proprietary formulation that enhances its strength and durability for long-term exposure to the sun and inclement weather
- Has a built-in fungicidal additive that inhibits fungus and mildew which is important for retarding stain and odor
- Resistant to most chemicals including many cleaning agents, solvents, alkalis, and acids (bleach may cause rapid discoloration)

Physical Properties	Results	Specification Limits
Color:	White	
Density:	1.66	1.55 - 2.20 lb/ft ³
Pore Size:	20	15 - 40 ppi
Tensile Strength:	14.4	8 psi min
Elongation:	90	70% min
Tear Strength:	2.9	2.0 lb/in ² min
CFD 60%:	0	N/A
50% Compression Set:	5.0	15% max
MVSS302 Flammability:		N/A
HF-1 ULH94 Flammability:		N/A
25% R IFD / ILD:	53	40-60 lbs
Permeability:		N/A

*All testing is done by the ASTM D 3574 Standard

*Product is made in the USA

All data and technical information are based on results achieved under the specific conditions defined according to the testing standards referenced. The products discussed are sold without representation or warranty, either expressed or implied. Foam N' More shall not be liable for any loss or damage resulting from inappropriate usage. It is the customer's responsibility to verify if the product is suitable for the intended application. The responsibility for professional and correct installation and compliance with relevant building regulations lies with the customer. Specifications may be changed at the discretion of Foam N' More without prior notification.